




OPK SERIES PUSH-IN FUSED TERMINAL BLOCKS OPK SERİSİ YAY BASKILI SİGORTALI RAY KLEMENSLER



PUSH IN

OPK - S 2,5

Order No: 2482



Dimensions Ölçüler (mm)	A	B	C	D
	68,3	33,0	34,5	5,9

MATERIAL / MATERYAL

Body / Gövde	PA6.6 V2
Bridge / Köprü	Copper / Bakır
Orange Button Turuncu Buton	PA6.6 V2
Spring / Yay	Stainless Steel / Paslanmaz Çelik
Temp./ Sıcaklık	-40 °C, +140 °C
Cable Strip L. / Soyma Boyu	9 mm

DATA / VERİ	TSE / CE
Voltage / Gerilim	750 V
Current / Akım	6,3 A
Section / Kesit	2,5 mm ²
Norm	EN-60947-7-1

RENKLER / COLOURS

RENK / COLOUR	Order No. / Sip.No.	Pcs. / Ad.
GREY / GRİ	2482	50
CREAM / KREM	2483	50
BLACK / SİYAH	2484	50
BLUE / MAVİ	2485	50
BROWN / K.RENGİ	2486	50
RED / KIRMIZI	2487	50
YELLOW / SARI	2488	50
GREEN / YEŞİL	2489	50

ACCESSORIES / AKSESUARLAR

Stopper / Durdurucu	1202,1222,1212
Group Sticker/ Grup Etiketi	1232
Marking / Markalama	9770 / 4440 / 4442 / 9540 / 7301
Glass Fuse / Cam Sigorta	WE-FS-52