



OPK SERIES PUSH-IN TYPE DOUBLE RAIL TERMINAL BLOCKS OPK SERİSİ YAY BASKILI TİP ÇİFT KATLI RAY KLEMENSLER

PUSH IN



OPK - C 2,5
Order No: 1782



Dimensions Ölçüler (mm)	A	B	C	D
	61,0	81,0	34,5	5,9

MATERIAL / MATERYAL

Body / Gövde	PA6.6 V2
Bridge / Köprü	Copper / Bakır
Orange Button Turuncu Buton	PA6.6 V2
Spring/Yay	Stainless Steel / Paslanmaz Çelik
Temp./Sıcaklık	-40 °C, +140 °C
Cable Strip L. / Soyma Boyu	9 mm

DATA / VERİ	TSE / CE	UL
Voltage / Gerilim	750 V	300 V
Current / Akım	24 A	16 A
Section / Kesit	2,5 mm ²	12 AWG
Norm	EN-60947-7-1	UL 1059

RENKLER / COLOURS

RENK/COLOUR	Order No./Sip.No.	Pcs./Ad.
GREY / GRİ	1782	50
CREAM / KREM	1783	50
BLACK / SİYAH	1784	50
BLUE / MAVİ	1785	50
BROWN/K.RENGİ	1786	50
RED / KIRMIZI	1787	50
YELLOW / SARI	1788	50
GREEN/YEŞİL	1789	50

ACCESSORIES / AKSESUARLAR

Cross Connection / Köprü	Order No./ Sip. No.	Section/ Kesit	Pcs./ Ad.
	1925	2,5 / 2	100
	1926	2,5 / 3	100
	1927	2,5 / 4	75
	1928	2,5 / 10	30
	1929	2,5 / 20	20
Stopper / Durdurucu	1202,1222,1212		
Group Sticker/Grup Etiketi	1232		
Marking/Markalama	9770 / 4440 / 4442 / 9540 / 7301		
Bridged / Köprülü	2572		
Diode / Diyotlu	2582		